

§ 38.25-3

(1) Maximum allowable pressure, as determined by the safety relief valve setting; or

(2) Design pressure, when cargo tanks operate at maximum allowable pressures reduced below the design pressure in order to satisfy special mechanical stress relief requirements.

NOTE: See the ASME Code, Section VIII, Appendix 3 for information on design pressure.

(c) For pressure vessels designed and/or supported such that they cannot safely be filled with water, the Commandant will consider a pneumatic test in lieu of the hydrostatic test. A leak test shall be performed in conjunction with the pneumatic test. Pneumatic testing shall be in accordance with subchapter F (Marine Engineering) of this chapter.

(d) Nonpressure vessel type tanks shall be tested to a pressure equal to the pressure on the bottom of the tank under the design conditions listed in § 38.05-4(e).

(e) In the application of the requirements for testing of the cargo tanks, the test shall in no case be less severe than the worst anticipated service condition of the cargo loading.

(f) In the design and testing of the independent cargo tanks, consideration shall be given to the possibility of the independent tanks being subjected to external loads.

[CGFR 66-33, 31 FR 15269, Dec. 6, 1966, as amended by CGD 85-061, 54 FR 50962, Dec. 11, 1989]

§ 38.25-3 Nondestructive testing—TB/ALL.

(a) Before nondestructive testing may be conducted to meet § 38.25-1 (a)(4) and (a)(5), the owner shall submit a proposal to the Officer in Charge, Marine Inspection for acceptance that includes—

(1) The test methods and procedures to be used, all of which must meet section V of the ASME Boiler and Pressure Vessel Code (1986);

(2) Each location on the tank to be tested; and

(3) The test method and procedure to be conducted at each location on the tank.

46 CFR Ch. I (10-1-07 Edition)

(b) If the Officer in Charge, Marine Inspection rejects the proposal, the Officer in Charge, Marine Inspection informs the owner of the reasons why the proposal is rejected.

(c) If the Officer in Charge, Marine Inspection accepts the proposal, then the owner shall ensure that—

(1) The proposal is followed; and

(2) Nondestructive testing is performed by personnel meeting ASNT "Recommended Practice No. SNT-TC-1A (1988), Personnel Qualification and Certification in Nondestructive Testing."

(d) Within 30 days after completing the nondestructive test, the owner shall submit a written report of the results to the Officer in Charge, Marine Inspection.

[CGD 85-061, 54 FR 50963, Dec. 11, 1989]

§ 38.25-5 Removal of defective tanks—TB/ALL.

If a tank fails to pass the tests prescribed in this subpart, it shall be removed from service unless otherwise authorized by the Commandant.

§ 38.25-10 Safety relief valves—TB/ALL.

(a) The cargo tank safety relief valves shall be inspected at least once in every 2 years.

(b) The safety relief valve discs must be lifted from their seats in the presence of a marine inspector by either liquid, gas, or vapor pressure at least once every 5 years to determine the accuracy of adjustment and, if necessary, must be reset.

[CGFR 66-33, 31 FR 15269, Dec. 6, 1966, as amended by CGD 95-027, 61 FR 26000, May 23, 1996]

PART 39—VAPOR CONTROL SYSTEMS

Subpart 39.10—General

Sec.

39.10-1 Applicability—TB/ALL.

39.10-3 Definitions—TB/ALL.

39.10-5 Incorporation by reference—TB/ALL.

39.10-9 Vessel vapor processing unit—TB/ALL.

39.10-11 Personnel training—TB/ALL.

39.10-13 Submission of vapor control system designs—TB/ALL.